

**Basic relay series**

See catalog data sheet for complete information.

**Mounting style and terminal type**

See catalog data sheet for complete information.

EXAMPLE:

**K - D2 A - 300 M**

**Coil code designator**

**AC COILS**

- E - 28 VAC 400Hz
- F - 115VAC 400Hz
- J - 28 VAC 50-400Hz
- K - 115VAC 50-400Hz

**DC COILS**

- A - 28 VDC
- B - 12 VDC
- C - 6 VDC
- M - 48 VDC
- N - 28 VDC suppressed coil
- R - 12 VDC suppressed coil
- V - 6 VDC suppressed coil
- W - 48 VDC suppressed coil

**Military dash number designations**

**MIL-PRF-6106\***

- 002 Standard MIL part
- 003 Standard MIL part with circuit breaker compatibility
- 102 Standard MIL part with established reliability screening
- 103 Standard MIL part with coil suppression and circuit breaker compatibility
- 104 Standard MIL part with established reliability screening, circuit breaker compatibility and coil suppression

**MIL-PRF-39016**

- 004 Standard MIL part with established reliability

**MIL-PRF-83536**

- 300 Standard MIL part with established reliability and circuit breaker compatibility; both suppressed and non-suppressed coils
- 304 Same as - 300 but supplied without internal arc suppression barriers

\* All subminiature product per MIL-PRF-6106 receive Established Reliability (ER) screening regardless of military number designation.

**Failure rate designator**

**MIL-PRF-39106**

- L - 3.0% / 10,000 operations
- M - 1.0% / 10,000 operations

**MIL-PRF-83536**

- L - 3.0% / 10,000 operations
- M - 1.0% / 10,000 operations