

Applicable Socket:
SO-1064-001

SM-1000-003



Application Notes:

101
102
103A
007
023

• Contact arrangement	2 PDT
• Qualified to (MIL Version)	MIL-PRF-83536/1 & 2

PRINCIPLE TECHNICAL CHARACTERISTICS

• Contacts rated at	Low level, 28 Vdc and 115/200 Vac, 400Hz, 3Ø, case grounded
• Weight	0.034 lbs. max
• Dimensions	0.41 in x 0.81 in x 0.64 in
• Special models available upon request	
• Hermetically sealed, corrosion resistant metal can	

CONTACT ELECTRICAL CHARACTERISTICS

Contact rating per pole and load type [1]	Load current in Amps		
	28 Vdc	115 Vac, 400 Hz, 1Ø	115/200 Vac, 400 Hz, 3Ø
Resistive	5	5	5
Inductive [2]	3	5	5
Motor	2	3	3
Lamp	1	1	-
Overload	20	30	30
Rupture	25	40	40
Low level [3]	-	-	-
Time current characteristics [4]	-	-	-

AMERICAS.

Tel: +1 714-736-7599
<http://www.esterline.com/powersystems>

EUROPE.

Tel: +33 3 87 97 31 01
Fax: +33 3 87 97 96 86

ASIA

Tel: +852 2 191 3830
Fax: +852 2 389 5803

COIL CHARACTERISTICS (Vdc)

CODE	A	B	C	M	N [5]	R [5]	V [5]
Nominal operating voltage	28	12	6	48	28	12	6
Maximum operating voltage	29	14.5	7.3	50	29	14.5	7.3
Maximum pickup voltage							
- Cold coil at +125° C	18	9	4.5	36	18	9	4.5
- During high temp test at +125° C	19.8	9.9	5	38	19.8	9.9	5
- During continuous current test at +125° C	22.5	11.25	5.7	42	22.5	11.25	5.7
Maximum drop-out voltage	7	4.5	2.5	14	7	7	2.5
Coil resistance in Ω $\pm 10\%$ at +25° C except types "C" and "V" +20%, - 10% $\pm 20\%$	500	125	20	1600	500	125	20


GENERAL CHARACTERISTICS

Temperature range	-70°C to +125°C
Minimum operating cycles (life) at rated load	100,000
Minimum operating cycles (life) at 25% rated load	400,000
Dielectric strength at sea level	
- All circuits to ground and circuit to circuit	1000 Vrms
- Coil to ground	1000 Vrms
Dielectric strength at altitude 80,000 ft	500 Vrms [6]
Insulation resistance	
- Initial (500 Vdc)	100 M Ω min
- After environmental tests (500 Vdc)	50 M Ω min
Sinusoidal vibration (A, D, and J mounting)	0.12 d.a. / 10 to 70 Hz 30G / 70 to 3000 Hz
Sinusoidal vibration (E mounting in track)	0.06 d.a. / 10 to 57 Hz 10G / 57 to 500 Hz 20G / 500 to 3000 Hz
Sinusoidal vibration (G mounting)	0.12 d.a. / 10 to 57 Hz 20G / 57 to 3000 Hz
Random vibration	
- Applicable specification	MIL-STD-202
- Method	214
- Test condition – A, D, and J mounting	1G (0.4G ² /Hz, 50 to 2000 Hz)
- Test condition – E and G mounting (E in track)	1E (0.2G ² /Hz, 50 to 2000 Hz)
- Duration	15 minutes each plane
Shock (A, D, and J mounting)	200G / 6 ms
Shock (E mounting in track)	50G / 6 ms
Shock (G mounting)	100G / 6 ms
Maximum contact opening time under vibration and shock	10 μ s
Operate time at nominal voltage @ 25°C	4 ms max
Release time at nominal voltage @ 25°C	4 ms max
Contact make bounce at nominal voltage @ 25°C	0.5 ms max
Contact release break bounce at nominal voltage @ 25°C	0.1 ms max [7]
Weight, maximum	0.034 lbs.


Unless otherwise noted, the specified temperature range applies to all relay characteristics.

Dimensions in inches
Tolerances, unless otherwise specified, ± 0.03 in


MOUNTING STYLES



RELAY HEIGHT MAY BE INCREASED .100 INCH FOR "N" SUPPRESSED COILS
MOUNTING STYLE A




RELAY HEIGHT MAY BE INCREASED .100 INCH FOR "N" SUPPRESSED COILS
MOUNTING STYLE D




RELAY HEIGHT MAY BE INCREASED .100 INCH FOR "N" SUPPRESSED COILS
MOUNTING STYLE E

NOTES:

FOR USE WITH TRACK MOUNT SYSTEMS, MT-5000-003 AND SM-1000-003
SOLDER SOCKET NOT PROVIDED ON THIS MOUNTING STYLE




RELAY HEIGHT MAY BE INCREASED .100 INCH FOR "N" SUPPRESSED COILS
MOUNTING STYLE G



RELAY HEIGHT MAY BE INCREASED .100 INCH FOR "N" SUPPRESSED COILS
MOUNTING STYLE J

Dimensions in inches
 Tolerances, unless otherwise specified, ± 0.03 in


TERMINAL TYPES



INSULATOR 1/4" PC-4699950-3 AVAILABLE FROM MOUSON ELECTRONICS, 540 W. 60TH ST., CA.


TERMINAL TYPE 1

FINISH:
 BODY – TIN/LEAD
 TERMINALS – TIN/LEAD




TERMINAL TYPE 2

FINISH:
 BODY – TIN/LEAD
 TERMINALS – TIN/LEAD



TERMINAL TYPE 4

FINISH:
 BODY – TIN/LEAD
 TERMINALS – GOLD PLATED



THIS END OF THE PIN WILL BE WITHIN A CIRCULAR TOLERANCE ZONE, THE DIAMETER OF WHICH WILL BE 0.100 (8 PLACES)


TERMINAL TYPE 7

FINISH:
 BODY – TIN/LEAD
 TERMINALS – TIN/LEAD


Dimensions in inches
Tolerances, unless otherwise specified, ± 0.03 in

DIAGRAMS


SCHEMATIC DIAGRAM



WIRING DIAGRAM




STANDARD TERMINAL LAYOUT



TOL: .XX ±.03; .XXX ±.010

NUMBERING SYSTEM



Example : X-A1A-XXX

X-A1A (Commercial)

X-A1A-300 L,M (MIL)

X-A1A-123 (Customer Part)

NOTES

- Standard Intermediate Current test applicable
- Inductive load life: 20,000 cycles.
- Low level endurance test: contact load of 10 to 50 millivolt, 10 to 50 microamp, 100 Ohm max. contact resistance.
- Refer to MIL-PRF-83536/1 & /2 for details.
- "N" "R" & "V" coils have back EMF suppression to 42 volts maximum.
- 500 Vrms with silicone rubber gasket compressed, 250 Vrms all other conditions.
- Applicable to Type "N", "R" & "V" coils only.
- Relay will not operate, but will not be damaged by application of reverse polarity on coil.
- Capacitive loads not applicable.

For any inquiries, please contact your local Esterline Power Systems representative
<http://www.esterline.com/powersystems/Contact/TheAmericas.aspx>